

UL 752 Specification for Bullet Resistant Materials

from Protective Structures, Ltd.

UL 752 Specifications & Ammunition

Rating	Ammunition	Grain	(g)	Minimum fps	Velocity m/s	shots fired	paragraph
Level 1	9mm full metal copper jacket with lead core	124	8	1175	358	3	4.3
Level 2	.357 Magnum jacketed lead soft point	158	10.2	1250	381	3	4.4
Level 3	.44 Magnum lead semi wad-cutter	240	15.6	1350	411	3	4.5
Level 4	.30 caliber rifle lead core	180	11.7	2540	774	1	4.6
Level 5	7.62mm rifle lead core full metal copper jacket military ball	150	9.7	2750	838	1	4.7
Level 6	9mm full metal copper jacket with lead core	124	8	1400	427	5	4.8
Level 7	5.56mm rifle full metal copper jacket with lead core	55	3.56	3080	939	5	4.9
Level 8	7.62mm rifle lead core full metal copper jacket military ball	150	9.7	2750	838	5	4.1
Supplementary Shotgun	12-gauge rifled lead slug 12-gauge 00 lead buck shot (12 pellets)	437 650	28.3 42	1585 1200	483 366	3	4.11

Maximum velocity is 110% of minimum velocity.

Paragraphs are listed in "UL 752 Paragraphs" page.

Note: When printing, be sure to print in *Landscape* mode for best results.

Protective Structures, Ltd.
7565 Industrial Court
Alpharetta, Georgia 30004
www.protectivestructures.com
info@protectivestructures.com

770.521.8666 phone
770.521.2299 fax